

MODELS

Colonial[™]105/110



warm. strong. classic.

Colonial wood doors give your home a warmth that endures year after year. These handcrafted doors are designed for easy operation and durability.

DOOR CONSTRUCTION

- Shiplap connections between sections provide a weathertight fit and smooth operation. Tracks and hardware are rust-resistant, hot-dipped galvanized steel.
- Individual door sections are 1-3/8" thick.
- Center panels are durable, 1/4" exterior-grade hardboard.
- Panel frames (rails and stiles) are made from high quality, kiln-dried West Coast hemlock, Sitka spruce or equal.
- Model 105: Standard duty rails and stiles. Model 110: Heavy duty rails and stiles.
- Mortise and tenon joints are glued and steel-pinned for lasting strength.

Specifications

Panel Designs

Single-car door designs. (optional windows shown).






4-2

4-4

Double-car door designs. (optional windows shown).



4-4

Available top selection designs.



4-8





2501 S. State Hwy. 121 Bus., Ste 200 Lewisville, TX 75067

wayne-dalton.com













Molded designs with inserts may not fit all panel sizes. Consult your Wayne Dalton dealer for availability.





Cathedral







Sunray

Plain Short Panel



*Other Stockton windows are available. Consult your dealer for details.

Plain Long Panel

Dimensions

(Stile/rail dimensions are face measurements and do not include the molding). All dimensions are nominal.

	COLONIAL 105		COLONIAL 110	
	ONE CAR	TWO CAR	ONE CAR	TWO CAR
Thickness	1-3/8"	1-3/8"	1-3/8"	1-3/8"
Top rail	2-7/8"	2-7/8"	4-7/8"	4-7/8"
Bottom rail	2-7/8"	4-7/8"	4-7/8"	4-7/8"
Combined meeting rail	2-1/4"	2-1/4"	4-1/2"	4-1/2"
End stile	2-7/8"	4-7/8"	4-7/8"	4-7/8"
Center stile	2-1/2"	2-1/2"	2-1/2"	2-12"

Limited Warranty

The manufacturer warrants wood doors will be free from defects in material and workmanship for a period of ONE YEAR from time of delivery. A copy of this limited warranty is available from your Dealer.

Dealer Imprint Area