



# Models 9100-5120-9605 (As-of Dec 2023)

Option Code	Positive Design PSF	Negative Design PSF	Maximum Size			Glazing Available	Approvals <sup>3</sup>			Wind Speed ASCE 7-16 ASCE 7-22 (MPH) Exposure B <sup>4</sup>	Wind Speed ASCE 7-16 ASCE 7-22 (MPH) Exposure C <sup>5</sup>		
			Max Door Width*	Max Door Height**	Section Height		Florida Approval	Miami-Dade Approval	TDI				
<a href="#">0640</a>	12.70	14.40	9'	12'	23.8"	Standard SP/LP	<a href="#">FL32360</a>	N/A	<a href="#">GDR-34</a>	N/A	120	95	
<a href="#">0641</a>	15.40	17.40	9'	12'	23.8"	Standard SP/LP				130	105		
<a href="#">0642</a>	18.40	20.80	9'	12'	23.8"	Standard SP/LP				145	115		
<a href="#">0643<sup>2</sup></a>	25.00	28.20	9'	12'	23.8"	Standard SP/LP, Impact SP/LP				170	135		
<a href="#">0644<sup>2</sup></a>	32.60	36.90	9'	12'	23.8"	Standard SP/LP, Impact SP/LP				190	155		
<a href="#">0645<sup>2</sup></a>	41.30	46.70	9'	12'	23.8"	Standard SP/LP, Impact SP/LP				215	175		
<a href="#">0234<sup>2</sup></a>	43.20	49.60	9'	8'-9"	20.8"	Standard SP, Impact SP/LP				220	180		
<a href="#">0646<sup>2</sup></a>	46.00	52.00	9'	12'	23.8"	Standard SP/LP, Impact SP/LP				230	185		
<a href="#">0647</a>	12.70	14.40	16'	12'	23.8"	Standard SP/LP				N/A	120	100	
<a href="#">0648</a>	15.40	17.40	16'	12'	23.8"	Standard SP/LP				<a href="#">FL32360</a>	N/A	<a href="#">GDR-34</a>	135
<a href="#">0649</a>	18.40	20.80	16'	12'	23.8"	Standard SP/LP	145	120					
<a href="#">0650</a>	23.00	25.00	16'	12'	23.8"	Standard SP/LP	165	135					
<a href="#">0651<sup>2</sup></a>	25.00	28.20	16'	12'	23.8"	Standard SP/LP, Impact SP/LP	170	140					
<a href="#">0230<sup>2</sup></a>	25.90	28.80	16'	8'-9"	20.8"	Standard SP/LP, Impact SP/LP	175	140					
<a href="#">0231<sup>2</sup></a>	30.00	33.50	16'	8'-9"	20.8"	N/A	185	155					
<a href="#">0235 Post<sup>2</sup></a>	39.20	43.70	16'	8'	20.8"	Standard SP, Impact SP/LP	215	175					
<a href="#">0634 Post</a>	39.20	43.70	16'	8'	23.8"	Impact SP/LP	Self-Cert	Self-Cert	210				175
<a href="#">0655</a>	12.70	14.40	18'	12'	23.8"	Standard SP/LP	<a href="#">FL32360</a>	N/A	120				100
<a href="#">0635</a>	15.30	17.00	18'	8'	23.8"	Standard SP/LP	Self-Cert	Self-Cert	130				110
<a href="#">0656</a>	18.40	20.80	18'	12'	23.8"	Standard SP/LP	<a href="#">FL32360</a>	<a href="#">GDR-34</a>	150	120			
<a href="#">0236 Post<sup>2</sup></a>	30.00	33.50	18'	8'	20.8"	Standard SP, Impact SP/LP	185		155				
<a href="#">0237 Post<sup>2</sup></a>	39.20	43.70	18'	8'	20.8"	Standard SP, Impact SP/LP	215		175				
<a href="#">0636 Post</a>	30.00	33.50	18'	8'	23.8"	Standard SP/LP	Self-Cert		Self-Cert	185	155		
<a href="#">0639 Post<sup>c</sup></a>	39.20	43.70	18'	8'	23.8"	N/A	Self-Cert	Self-Cert	215	175			

- [Jamb Connection Supplement- FL 32360](#)
- [Post Installation Instructions -FL 9174](#)
- [Jamb Connection Supplement- FL 9174](#)
- [Track Supplement Chart - FL 9174](#)

- All doors tested for uniform static air pressure per ANSI/DASMA 108 to test pressure of 1.5 x design pressure
- Also tested for large missile impact and cyclic wind pressure per ANSI/DASMA 115
- FBC - Florida Building Commission, TDI - Texas Department of Insurance
- Wind Speed is 3-Second Peak gusts, using exposure B, for single or double story structures, calculated according to ASCE 7-22. Assumptions: Mean roof height of 25 ft, flat ground, sea level, enclosed building and roof angle >10°. The Wind Speed Calculation is based on the max width of the door and a max height of 8-7 ft depending on the section heights. If a narrower, or taller door is used instead of the max shown in the chart, the wind speed rating may be different. For reference only. Final door requirements to be determine by architect, engineer or other professional.
- Wind Speed is 3-Second Peak gusts, using exposure C, for single or double story structures, calculated according to ASCE 7-22. Assumptions: Mean roof height of 25 ft, flat ground, sea level, enclosed building and roof angle >10°. The Wind Speed Calculation is based on the max width of the door and a max height of 8-7 ft depending on the section heights. If a narrower, or taller door is used instead of the max shown in the chart, the wind speed rating may be different. For reference only. Final door requirements to be determined by architect, engineer or other professional.
- Standard SP/LP** - Short (Single Colonial, Single Sonoma) and long (Double Sonoma, Ranch) panel glazing is not impact resistant and does not meet the requirements for Wind-Borne Debris Regions.  
**Impact SP/LP** - Short (Single Colonial, Single Sonoma) and long (Double Sonoma, Ranch) is impact resistant and does meet the requirements for Wind-Borne Debris Regions.
- Doors only available in greater than 7' heights.
- Low Head Room track is available.
- All panel styles available.
- Sonoma Ranch Glazing Available with select Option Codes.
- Wind speeds listed in this guide are provided for reference purposes only. In **ALL** cases the local building authority is the sole and final determiner of the structural and safety requirements, and suitability of the garage door.